


Input data

Refrigerant	R134a	
Reference temperature	Dew point temperature	
Calculation mode	Refrigeration / Air Cond.	
Operating mode	Subcritical	
Power supply	400/3/50	
Condensing temperature	°C	45
Condensing pressure	bar	11.6
Liquid subcooling	K	2
Liquid temperature	°C	43
Evaporating temperature	°C	-5
Evaporating pressure	bar	2.43
Suction gas temperature	°C	20
Evaporator superheating	K	5



Output data

Compressor :	CXH02-120-340Y	
Number of compressors :	FSx1	
Refrigerating capacity	kW	148.861
Refrigerating capacity [*ref]	kW	142.36
Evaporator capacity	kW	131.984
Power input	W	52167
Condenser capacity, theor.	kW	201.028
Current	A	90.78
COP/EER	W/W	2.53
Mass flow	kg/h	3436
Operating frequency	Hz	50
Connection	-	PWS
Operating mode	-	100%
Discharge temperature	°C	89.8
Ratio (%)	%	100.0%
Note	-	
Oil flow	l/min	12.63
Heat Exchanged (oil Cooler)	kW	-
Oil Temp. at Oil Cooler Outlet	°C	-
Certified by	-	Frascold


Certified by:

- Frascold tentative data

Legend:

- *ref: At conditions according to EN12900
- Suction gas superheating = 10 K
- Liquid subcooling = 0 K

P&I Diagram:



Oil separator:

Name	WK201
Number of separators	1

Results

Number of compressors, maximum		3
Utilization (Number of separators)	%	33.33
Refrigerant mass flow, maximum	kg/h	5279
Utilization (Refrigerant mass flow)	%	65.09
Oil flow, maximum	l/min	112.5
Utilization (Oil flow)	%	11.23

Selection parameters

Number of compressors		1
Mass flow, Compressors	kg/h	3436
Oil flow, Compressors	l/min	12.63

Operating conditions

Evaporating temperature	°C	-5
Suction gas temperature	°C	20
Condensing temperature	°C	45
Liquid temperature	°C	43

All data subject to change without notice

Model: CXH02-120-340Y

Refrigerant: R134a

Power supply: 400/3/50 PWS

Technical data:


Displacement	340 m³/h
Nominal compressor speed	2900 rpm
Motor voltage	400 V
Nominal operating frequency	50 Hz
Maximum allowed operating current (MRA)	195 A
Locked rotor current (LRA)	505 A
Locked rotor current (LRA), DOL	793 A
Net weight	563 kg
Lubricant	FRASCOLD POE170
Oil charge	11 l
Maximum static pressure LP	20.5 bar
Maximum operating pressure HP	30 bar

Sound level:

Sound power level 5/50°C R407C @50Hz	89.4 dB(A)
Sound pressure (*) - Distance: 1 m	81.4 dB(A)
Sound power level 5/50°C R134a @50Hz	86 dB(A)
Sound pressure (*) - Distance: 1 m	78 dB(A)

*half sphere model

Motor connections:




All data subject to change without notice

Model: CXH02-120-340Y

Refrigerant: R134a

Power supply: 400/3/50 PWS

Dimensions:



Legend:

SV: Suction Valve	3 1/8" in - 80 mm	6: Crankcase heater	-
DV: Discharge valve	2 1/8" in - 54 mm	7: Oil level regulator connection	3/4" NPT
SL: Suction line	3 1/8"	8: Oil level sight glass	-
V1: Capacity control valve	-	9: Filter clogging sensor connection	1/2" GAS
V2: Capacity control valve	-	10: Oil cooler connection	1/2" NPT
V3: Capacity control valve	-	11: Oil drain plug	1/4" NPT
1: High pressure connection	1/8" NPT	12: Oil drain valve	1/8" NPT
2: Low pressure connection	1/8" NPT	13: Maximum oil temperature sensor	-
3: High pressure connection	1/4" SAE x 1/4" SAE	14: ECO/liquid injection connection	1 1/8"
4: Low pressure connection	1/4" SAE x 1/4" SAE	NP: Nameplate	
5: Oil charge plug	3/8" GAS		

All data subject to change without notice

Model: CXH02-120-340Y

Refrigerant: R134a

Power supply: 400/3/50 PWS

Polynomial coefficients according to EN12900 for CXH02-120-340Y:

*S = T_{evap} ; D = T_{cond}

Reference conditions

Refrigerant	R134a
Ambient temperature	35 °C
Suction gas superheating	10 K
Liquid subcooling	0 K
Frequency	50 Hz

	Refrigerating capacity [W]	Power input [W]
C1	2.284450E+005	3.641138E+004
C2	8.179460E+003	1.108632E+003
C3	1.462220E+003	3.280472E+001
C4	1.256030E+002	2.260963E+001
C5	7.156760E+001	-2.494083E+001
C6	-7.614140E+001	5.972552E+000
C7	3.222000E-001	2.445787E-001
C8	-1.598290E-001	-3.455528E-001
C9	-1.640830E+000	2.457747E-001
C10	4.364080E-001	4.893543E-002

$$Y = C1 + C2*S + C3*D + C4*S^2 + C5*S*D + C6*D^2 + C7*S^3 + C8*D*S^2 + C9*S*D^2 + C10*D^3$$