


## Input data

Refrigerant	R449A	
Reference temperature	Dew point temperature	
Calculation mode	Refrigeration / Air Cond.	
Operating mode	Subcritical	
Power supply	400/3/50	
Condensing temperature	°C	45
Condensing pressure	bar	18.86
Liquid subcooling	K	2
Liquid temperature	°C	38.72
Evaporating temperature	°C	-5
Evaporating pressure	bar	4.33
Suction gas temperature	°C	20
Evaporator superheating	K	5



## Output data

<b>Compressor :</b>		<b>D2-15.1Y</b>
Number of compressors :		FSx1
Refrigerating capacity	kW	9.413
Refrigerating capacity [ *ref ]	kW	9.216
Evaporator capacity	kW	8.337
Power input	W	3509
Condenser capacity, theor.	kW	12.923
Current	A	6.43
COP/EER	W/W	2.38
Mass flow	kg/h	211
Operating frequency	Hz	50
Connection	-	DOL-STAR
Operating mode	-	100%
Discharge temperature	°C	99.28
Ratio (%)	%	100.0%
Note	-	
Oil flow	l/min	-
Heat Exchanged (oil Cooler)	kW	-
Oil Temp. at Oil Cooler Outlet	°C	-
Certified by	-	Frascold


### Certified by:

- Frascold tentative data

### Legend:

- \*ref: At conditions according to EN12900
- Suction gas temperature = 20 °C
- Liquid subcooling = 0 K

**P&I Diagram:**



**Model: D2-15.1Y**

Refrigerant: R449A

Power supply: 400/3/50 DOL-STAR

**Technical data:**


Displacement	15.36 m³/h
Nominal compressor speed	1450 rpm
Motor voltage	400 V
Nominal operating frequency	50 Hz
Maximum allowed operating current (MRA)	8.4 A
Locked rotor current (LRA)	35.9 A
Number of pistons	2
Net weight	45 kg
Lubricant	FRASCOLD POE32
Oil charge	1.1 l
Maximum static pressure LP	20.5 bar
Maximum operating pressure HP	30 bar

**Sound level:**

Sound power level -10/45°C R404A @50Hz	66.5 dB(A)
Sound pressure (*) - Distance: 1 m	58.5 dB(A)
Sound power level -35/40°C R404A @50Hz	69 dB(A)
Sound pressure (*) - Distance: 1 m	61 dB(A)

\*half sphere model

**Motor connections:**




*All data subject to change without notice*

**Model: D2-15.1Y**

Refrigerant: R449A

Power supply: 400/3/50 DOL-STAR

**Dimensions:**



**Legend:**

SV: Suction Valve	7/8" in - 22.225 mm	M: Discharge valve	192 mm
DV: Discharge valve	5/8" in - 16 mm	N: Discharge valve	13 mm
A: Length	369 mm	1: High pressure connection	1/8" NPT
B: Width	242 mm	2: Low pressure connection	1/8" NPT
C: Height	294 mm	3: Oil charge plug	1/4" GAS
D: Base mounting	234 mm	4: Oil level sight glass	-
E: Base mounting	194 mm	5: Crankcase heater seat	-
F: Suction Valve	165 mm	6: Oil drain plug	M8 x 22
G: Suction Valve	221 mm	12: Oil return plug	1/8" NPT
H: Suction Valve	42 mm	NP: Nameplate	
L: Discharge valve	94 mm		

All data subject to change without notice

**Model: D2-15.1Y**

Refrigerant: R449A

Power supply: 400/3/50 DOL-STAR

**Polynomial coefficients according to EN12900 for D2-15.1Y:**

\*S = T<sub>evap</sub> ; D = T<sub>cond</sub>

Reference conditions	
Refrigerant	R449A
Ambient temperature	35 °C
Suction gas temperature	20 °C
Liquid subcooling	0 K
Frequency	50 Hz

	Refrigerating capacity [W]	Power input [W]
<b>C1</b>	1.932880E+004	7.083440E+002
<b>C2</b>	7.130760E+002	-5.792230E+001
<b>C3</b>	-1.680960E+002	9.257970E+001
<b>C4</b>	9.291940E+000	-1.752990E+000
<b>C5</b>	-5.454840E+000	2.650910E+000
<b>C6</b>	-2.331440E-001	-5.615610E-001
<b>C7</b>	4.207070E-002	-1.369870E-002
<b>C8</b>	-5.770490E-002	1.698810E-002
<b>C9</b>	-5.479090E-003	-6.204750E-003
<b>C10</b>	4.849340E-004	4.291350E-004

$$Y = C1 + C2*S + C3*D + C4*S^2 + C5*S*D + C6*D^2 + C7*S^3 + C8*D*S^2 + C9*S*D^2 + C10*D^3$$