



## Product Code

# 8394/B

Valve Core

Internal Spring Tmax= 90° C MWP=28bar

PS = 35 bar

### Product use

Accessories for use with the following ASHRAE 34:2019 refrigerants, Class A1, A2L, or A3:

- HCFC (R22)
- HFC (R134a, R32, R404A, R407C, R410A, R507)
- HFO and HFO/HFC blends (R1234ze, R1234yf, R448A, R449A, R450A, R452A, R513A, R515A, R515B)
- HC (R290, R600, R600a, R1270)
- R744

Operating pressures vary based on the refrigerants.

### Product details

Connections SAE Flare M	-
Connections SAE Flare F	-
Static pressure [bar]	35
Working pressure [bar]	30
PS [bar]	-
TS [°C] min.	-35
TS [°C] max.	+100
Use	R22HFC
Package pcs	100

### Notes

- (1) Inside spring
- (2) Outside spring

*Castel non si assume alcuna responsabilità per eventuali errori nei cataloghi, opuscoli e altro materiale stampato o indicato nel sito Castel.it. Castel si riserva il diritto di modificare i propri prodotti senza preavviso. Tutti i marchi in questo materiale sono di proprietà di Castel. Tutti i diritti riservati.*

*Castel assumes no responsibility for any errors in catalogs, brochures and other material printed or indicated on the Castel.it website. Castel reserves the right to modify its products without notice. All trademarks in this material are the property of Castel. All rights reserved.*

(3) NB: No use with R22