

| Part-No. | Type              |
|----------|-------------------|
| 141384   | FN063-SDK.4I.V7P1 |

Axial fan with sickle blades  
with guard grille for short bell mouth  
Type:FN063-SDK.4I.V7P1  
3~ 400V  $\pm 10\%$  D/Y 50Hz P1 0,62/0,44kW  
1,25/0,72A DI=15% 900/720rpm COSY 0,72 70°C  
3~ 400V  $\pm 10\%$  D/Y 60Hz P1 0,94/0,52kW  
1,6/0,88A DI=5% 980/640rpm COSY 0,85 50°C  
3~ 460V  $\pm 10\%$  D/Y 60Hz P1 1,00/0,64kW  
1,55/0,94A DI=5% 1040/730rpm COSY 0,82 50°C  
IP54 THCL 155  
ErP conform 2015  
N=41,6  
statA=33,8%  
Terminal box K62  
Mounted on Stator.  
wiring diagram: 1360-108XA  
Rating plate: 1x fixed  
Fitting position H/Vu/Vo.  
Motor protection: thermal contact  
Operating mode: Continuous operation with occasional starts  
according to DIN EN 60034-1:2011-02.  
Occasional starting between -40 °C and -25 °C is permissible  
Continuous operation below -25 °C only with special bearings  
for refrigeration applications on request.  
Moisture and hot climate protection.  
ball bearing with long-time lubrication.  
blades made of aluminium.  
Stator unpainted  
Rotor unpainted  
Blades unpainted  
Motor suspension powder-coated RAL 9005 (jet black)  
resistance class 2 (L-TI-0585).  
ring grill

---