



COD. COPELAND			BN659403 00			MOD.	M0.72.01		
N°	COMP.	COD.	DESCRIZIONE ITALIANO	COMP.	COD.	ENGLISH DESCRIPTION		CARATTERISTICHE TECNICHE - TECHNICAL FEATURES	
1	SERIE	SD	SPILLONE NTC PER INFILZARE CON IMPUGNATURA IN TERMOPLASTICO (2 FILI)	SERIES	SD	PROBE FOR PIERCEING NTC WITH THERMOPLASTIC HANDGRIP (2 WIRES)		CAMPO DI LAVORO OPERATING RANGE	(-50+110)°C
2	ELEMENTO	N	NTC 10K ±1% B3435 1% DISCRETO	ELEMENT	N	NTC 10K ±1% B3435 1% DISCRETE		PRECISIONE TOLERANCE	1%
3	MATERIALE CAP.	A	AISI 304	MATERIAL CASE	A	AISI 304		GRADO DI PROTEZIONE	IP 67
4	LUNGHEZZA CAP.	10	100 mm	LENGHT CASE	10	100 mm		PROTECTION GRADE	
5	Ø CAP.	C	CONICO (DA Ø5,5 - A Ø3,5)	Ø CASE	C	CONICAL (FROM Ø5,5 - TO Ø3,5)			
6	CABLE	FC	GOMMA TERMOPLASTICA (EST) POLIPROP. (INT) [9CAVSAN011]	CABLE	FC	THERMOPLASTIC RUBBER (EST) POLY. (INT) [9CAVSAN011]		TESTS	
6A	COLOR		CAVO (GRIGIO) ANIME (NERO-BIANCO)	COLOR		CABLE (GREY) LEADS (BLACK-WHITE)		TRAZIONE CAVO-CAPSULA TRACTION CABLE-CASE	kg 2/24 h
6B	DIMENSIONI		SEZIONE 2X0.22 MM² Ø3.3 MM	DIMENSIONS		SECTION 2X0.22 MM² Ø3.3 MM		VALORE RESISTIVO A OHMIC CHECK	
7	LUNGH.SONDA	30	3 METRI	PROBE LENGHT	30	3 METERS		RESISTENZA DI ISOLAMENTO INSULATION DEGREE	20 Mohm 500 Vcc
8	RACCORDO CAVO/CAPSULA	N	NESSUNO	CONNECTOR CABLE/CASE	N	NONE		RIGIDITA' DIELECTRIC STRENGTH	
9	TERMINALI	P	PUNTALI [9TERVAR007]	TERMINALS	P	PINS [9TERVAR007]		DATE	30/08/2024
10	RIEMPITIVO	S	RESINA POLIURETANICA	FILLING	S	POLYURETANIC RESIN			
11	OPZIONI	vmie	PUNTA ACUMINATA - MATASSATA - IN SACCHETTO - CON ETICHETTA	OPTIONS	vmie	NEEDLE TIP - HANK - INSIDE SMALL BAG - WITH LABEL			
12	EXTRA	1xmie -	1 PZ X SACCHETTO CON ETICHETTA - -	EXTRAS	1xmie -	1 PC PER BAG WITH LABEL - -			